

# LKRA-VPA, BKRA-VPA series (wheel Ø 125–150 mm)

## Light duty castors with bolt hole, wheel with solid rubber tyres



1

100–120 kg

**Bracket:** LKRA/BKRA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Swivel bracket:**


- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** VPA series

- tyre: high-quality solid rubber, hardness 80 Shore A, colour grey, non-marking, non-staining
- rim: high-quality nylon 6 or polypropylene in the electrically conductive version “-EL”, impact resistant, colour black

**Additional details:**

- bracket series: page 86
- brakes: page 112–113
- wheel series: page 127
- bearing types: page 84–85



Swivel castors	Fixed castors	Swivel castors with “stop-fix” brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LKRA-VPA 125G	BKRA-VPA 125G	LKRA-VPA 125G-FI	125	25	100	plain bore	158	57	13	40
LKRA-VPA 125G-11		LKRA-VPA 125G-11-FI	125	25	100	plain bore	158	57	11	40
LKRA-VPA 125K	BKRA-VPA 125K	LKRA-VPA 125K-FI	125	25	100	ball bearing	158	57	13	40
LKRA-VPA 125K-11		LKRA-VPA 125K-11-FI	125	25	100	ball bearing	158	57	11	40
LKRA-VPA 126G	BKRA-VPA 126G	LKRA-VPA 126G-FI	125	32	120	plain bore	158	57	13	40
LKRA-VPA 126G-11		LKRA-VPA 126G-11-FI	125	32	120	plain bore	158	57	11	40
LKRA-VPA 126K	BKRA-VPA 126K	LKRA-VPA 126K-FI	125	32	120	ball bearing	158	57	13	40
LKRA-VPA 126K-11		LKRA-VPA 126K-11-FI	125	32	120	ball bearing	158	57	11	40
LKRA-VPA 150G	BKRA-VPA 150G	LKRA-VPA 150G-FI	150	30	110	plain bore	182	57	13	40
LKRA-VPA 150G-11		LKRA-VPA 150G-11-FI	150	30	110	plain bore	182	57	11	40
LKRA-VPA 150K	BKRA-VPA 150K	LKRA-VPA 150K-FI	150	30	110	ball bearing	182	57	13	40
LKRA-VPA 150K-11		LKRA-VPA 150K-11-FI	150	30	110	ball bearing	182	57	11	40

For stainless steel versions, see page 392

### Versions / options



	electrically conductive version, black tyre	with thread guard, pressed steel, zinc-plated	with threaded pin M12 x 30	with synthetic expander fitting	with metal expander fitting	buffers
Technical description page	50	116	104	105	105	116
<b>Product code suffix</b>	<b>-EL</b>	<b>-FA</b>	<b>-GS12</b>	<b>see page 148</b>	<b>see page 148</b>	<b>AG / ARG series</b>
Available for	all ball bearing versions*	all	swivel castors with bolt hole Ø 13 mm	swivel castors with bolt hole Ø 11 mm (except EL)	swivel castors with bolt hole Ø 11 mm	see page 148

\* Wheel load capacity of electrically conductive version reduced by 25%