

LPA-POA, BPA-POA, LKPA-POA, BKPA-POA series

Light duty castors with top plate, with nylon wheel



70–120 kg

Bracket: LPA/BPA, LKPA/BKPA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

Swivel bracket:

- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process
- synthetic “stop-fix” brake lever for series LPA, steel brake lever for series LKPA


Wheel: POA series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour black

Additional details:

- bracket series: page 86
- brakes: page 112–113
- wheel series: page 143
- bearing types: page 84–85

1



Swivel castors	Fixed castors	Swivel castors with “stop-fix” brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LPA-POA 35G		LPA-POA 35G-RA *	35	25	75	plain bore	52	60 x 60	38 x 38 / 48 x 48	6.2	15
LPA-POA 50G	BPA-POA 50G	LPA-POA 50G-FI **	50	18	75	plain bore	71	60 x 60	38 x 38 / 48 x 48	6.2	23
LKPA-POA 52G		LKPA-POA 52G-RA *	50	29	120	plain bore	73	90 x 66	75 x 45 / 61 x 51	8.5	29
LPA-POA 75G	BPA-POA 75G	LPA-POA 75G-FI **	75	23	75	plain bore	100	60 x 60	38 x 38 / 48 x 48	6.2	29
LKPA-POA 80G	BKPA-POA 80G	LKPA-POA 80G-FI	80	32	120	plain bore	111	90 x 66	75 x 45 / 61 x 51	8.5	40
LPA-POA 102G		LPA-POA 102G-FI **	100	22	70	plain bore	123	60 x 60	38 x 38 / 48 x 48	6.2	33
LKPA-POA 100K	BKPA-POA 100K	LKPA-POA 100K-FI	100	30	120	ball bearing (C)	136	90 x 66	75 x 45 / 61 x 51	8.5	40
LKPA-POA 100G	BKPA-POA 100G	LKPA-POA 100G-FI	100	32	120	plain bore	136	90 x 66	75 x 45 / 61 x 51	8.5	40
LKPA-POA 125K	BKPA-POA 125K	LKPA-POA 125K-FI	125	30	120	ball bearing (C)	161	90 x 66	75 x 45 / 61 x 51	8.5	40
LKPA-POA 125G	BKPA-POA 125G	LKPA-POA 125G-FI	125	32	120	plain bore	161	90 x 66	75 x 45 / 61 x 51	8.5	40
LKPA-POA 150G	BKPA-POA 150G	LKPA-POA 150G-FI	150	32	110	plain bore	185	90 x 66	75 x 45 / 61 x 51	8.5	40

* “Radstop” brake version

** Synthetic brake lever, see image below

For stainless steel versions, see page 397

Versions / options



	with synthetic brake lever	“Radstop” wheel brake
Technical description page		
Product code suffix		
Available for	series LPA...-FI as standard	series LPA Ø 35 mm series LKPA Ø 50 mm