

## LWGX-TPA series

**Blickle WAVE synthetic castors, corrosion-resistant, with bolt hole, colour silver grey, wheel with thermoplastic rubber tread**



100–110 kg

-20 °C to +60 °C

**Bracket:** LWGX series

- high-quality nylon 6, impact resistant
- moulded corrosion-resistant grooved ball bearing in the swivel head sealed on both sides
- bolt hole
- colour silver grey RAL 7001
- all parts including axle material are corrosion-resistant
- modern, appealing design

**Wheel:** TPA series

- tread: high-quality thermoplastic rubber-elastomer (TPE), hardness 85 Shore A, colour grey, non-marking, oil containing
- wheel centre: high-quality polypropylene, impact resistant, colour silver grey RAL 7001

**Other features:**


- the load capacity reduces at ambient temperatures above +30 °C

**Additional details:**

- bracket series: page 88
- brakes: page 112–113
- wheel series: page 60
- bearing types: page 84–85



2



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LWGX-TPA 101G	LWGX-TPA 101G-FI	100	32	100	plain bore	135	55	13	38
LWGX-TPA 101G-11	LWGX-TPA 101G-11-FI	100	32	100	plain bore	135	55	11	38
LWGX-TPA 101XKF	LWGX-TPA 101XKF-FI	100	32	100	ball bearing (C)	135	55	13	38
LWGX-TPA 101XKF-11	LWGX-TPA 101XKF-11-FI	100	32	100	ball bearing (C)	135	55	11	38
LWGX-TPA 126G	LWGX-TPA 126G-FI	125	32	110	plain bore	160	55	13	40
LWGX-TPA 126G-11	LWGX-TPA 126G-11-FI	125	32	110	plain bore	160	55	11	40
LWGX-TPA 126XKF	LWGX-TPA 126XKF-FI	125	32	110	ball bearing (C)	160	55	13	40
LWGX-TPA 126XKF-11	LWGX-TPA 126XKF-11-FI	125	32	110	ball bearing (C)	160	55	11	40

**Versions / options \***



	plain bore version	electrically-conductive version, non-marking, grey	with threaded pin made from stainless steel M10 x 20	with threaded pin made from stainless steel M12 x 20	with synthetic expander fitting	in special colour
Technical description page		50	104	104	105	
Product code suffix		LWGXE-...-ELS	-GSX10	-GSX12	see page 168	
Available for		all ball bearing versions**	all with bolt hole Ø 13 mm	all with bolt hole Ø 13 mm	bolt hole Ø 11 mm upon request***	upon request

\* Other versions / options: buffers AW / AG / ARG series; rotating buffers -AMWX / -AMGX series see page 169 (technical information on page 116)

\*\* Load capacity of electrically conductive version reduced by 35%

\*\*\* Not for electrically conductive version; Total height +3 mm