

## LE-TPA, B-TPA series

### Pressed steel castors with top plate, wheel with thermoplastic rubber tread



100–250 kg

**Bracket:** LE/B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Swivel bracket:**


- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** TPA series

- tread: high-quality thermoplastic rubber-elastomer (TPE), hardness 85 Shore A, colour grey, non-marking, oil containing
- wheel centre: high-quality polypropylene, impact resistant, colour silver grey ("ELS" version colour black)

**Additional details:**

- bracket series: page 90
- brakes: page 112–113
- wheel series: page 186
- bearing types: page 84–85



Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LE-TPA 80G	B-TPA 80G	LE-TPA 80G-FI	80	32	100	plain bore	102	100 x 85	80 x 60	9	38
LE-TPA 80KF	B-TPA 80KF	LE-TPA 80KF-FI	80	32	100	ball bearing (C)	102	100 x 85	80 x 60	9	38
LE-TPA 102G	B-TPA 102G	LE-TPA 102G-FI	100	32	110	plain bore	125	100 x 85	80 x 60	9	36
LE-TPA 102KF	B-TPA 102KF	LE-TPA 102KF-FI	100	32	110	ball bearing (C)	125	100 x 85	80 x 60	9	36
LE-TPA 127G	B-TPA 127G	LE-TPA 127G-FI	125	32	125	plain bore	150	100 x 85	80 x 60	9	38
LE-TPA 127KF	B-TPA 127KF	LE-TPA 127KF-FI	125	32	125	ball bearing (C)	150	100 x 85	80 x 60	9	38
LE-TPA 160G	B-TPA 160G	LE-TPA 160G-FI	160	40	200	plain bore	195	140 x 110	105 x 75–80	11	54
LE-TPA 160R	B-TPA 160R	LE-TPA 160R-FI	160	40	200	roller bearing	195	140 x 110	105 x 75–80	11	54
LE-TPA 200G	B-TPA 200G	LE-TPA 200G-FI	200	40	250	plain bore	235	140 x 110	105 x 75–80	11	54
LE-TPA 200R	B-TPA 200R	LE-TPA 200R-FI	200	40	250	roller bearing	235	140 x 110	105 x 75–80	11	54

For stainless steel versions, see page 399

### Versions / options



	plain bore version	electrically conductive version, non-marking grey	large thread guard with additional ball bearing seals	with steel foot guard
Technical description page		50	85	116
<b>Product code suffix</b>		<b>-ELS</b>	<b>-KFD</b>	<b>-FS</b>
Available for		all plain bore and ball bearing versions*	all ball bearing versions	wheel Ø 100–200 mm upon request

\* Wheel load capacity of electrically conductive version reduced by 35%