

LER-POEV series

**Pressed steel castors with bolt hole,
wheel with "Blickle EasyRoll" elastic solid rubber tyre**



120–300 kg

Bracket: LER series


- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: POEV series

- tyre: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, colour black
- wheel centre: high-quality nylon 6, impact resistant, colour black

Additional details:

- bracket series: page 91
- brakes: page 112–113
- wheel series: page 212–213
- bearing types: page 84–85



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LER-POEV 60KF	LER-POEV 60KF-RA *	60	34	120	ball bearing (CC)	80	70	13	35
LER-POEV 80G	LER-POEV 80G-FI	80	32	140	plain bore	102	70	13	38
LER-POEV 80R	LER-POEV 80R-FI	80	32	140	roller bearing	102	70	13	38
LER-POEV 80KF	LER-POEV 80KF-FI	80	32	140	ball bearing (C)	102	70	13	38
LER-POEV 100G	LER-POEV 100G-FI	100	32	150	plain bore	125	70	13	36
LER-POEV 100R	LER-POEV 100R-FI	100	32	150	roller bearing	125	70	13	36
LER-POEV 100KA	LER-POEV 100KA-FI	100	32	150	ball bearing (C)	125	70	13	36
LER-POEV 125G	LER-POEV 125G-FI	125	37	150	plain bore	150	70	13	38
LER-POEV 125R	LER-POEV 125R-FI	125	37	150	roller bearing	150	70	13	38
LER-POEV 125KA	LER-POEV 125KA-FI	125	37	150	ball bearing (C)	150	70	13	38
LER-POEV 161R	LER-POEV 161R-FI	160	40	300	roller bearing	195	88	13	54
LER-POEV 161KA	LER-POEV 161KA-FI	160	40	300	ball bearing (C)	195	88	13	54
LER-POEV 160R	LER-POEV 160R-FI	160	50	300	roller bearing	195	88	13	54
LER-POEV 160KA	LER-POEV 160KA-FI	160	50	300	ball bearing (CC)	195	88	13	54
LER-POEV 201R	LER-POEV 201R-FI	200	40	300	roller bearing	235	88	13	54
LER-POEV 201KA	LER-POEV 201KA-FI	200	40	300	ball bearing (C)	235	88	13	54
LER-POEV 200R	LER-POEV 200R-FI	200	50	300	roller bearing	235	88	13	54
LER-POEV 200KA	LER-POEV 200KA-FI	200	50	300	ball bearing (CC)	235	88	13	54

* "Radstop" brake version

For stainless steel versions, see page 404

Versions / options



	with non-marking grey tyre	with non-marking blue tyre	electrically conductive version, black tyre	with thread guard, pressed steel, zinc-plated	with stainless steel roller bearing / ball bearing	with steel foot guard	truck lock
Technical description page	52	53	50	116	84 / 85	116	114
Product code suffix	-SG	-SB	-EL	-FA	-XR / -XKA / XKF	-FS	FF 100-1 / FF 125-1
Available for	all	wheel Ø 80–125, 160x50, 200x50 mm	ball bearing versions upon request	all, with exception of versions with KF and wheel width 40 mm	see versions / options page 212–213	upon request	wheel Ø 100+125 mm