

## LKR-POEV series

**Pressed steel castors, heavy-duty design, with bolt hole, wheel with "Blickle EasyRoll" elastic solid rubber tyre**



170–250 kg

**Bracket:** LKR series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** POEV series


- tyre: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, colour black
- wheel centre: high-quality nylon 6, impact resistant, colour black

**Additional details:**

- bracket series: page 92
- brakes: page 112–113
- wheel series: page 212–213
- bearing types: page 84–85



3



Swivel castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LKR-POEV 82KF	LKR-POEV 82KF-FI	80	40	170	ball bearing (C)	110	88	13	40
LKR-POEV 100R	LKR-POEV 100R-FI	100	32	200	roller bearing	130	88	13	45
LKR-POEV 100KA	LKR-POEV 100KA-FI	100	32	200	ball bearing (C)	130	88	13	45
LKR-POEV 125R	LKR-POEV 125R-FI	125	37	250	roller bearing	155	88	13	48
LKR-POEV 125KA	LKR-POEV 125KA-FI	125	37	250	ball bearing (C)	155	88	13	48

### Versions / options



	with non-marking grey tyre	with non-marking blue tyre	electrically conductive version, black tyre	with thread guard, pressed steel, zinc-plated	with stainless steel roller bearing / ball bearing	small thread guard with additional ball bearing seal	truck lock
Technical description page	52	53	50	116	84 / 85	85	114
<b>Product code suffix</b>	<b>-SG</b>	<b>-SB</b>	<b>-EL</b>	<b>-FA</b>	<b>-XR / -XKA / XKF</b>	<b>-KAD</b>	<b>FF 100-1 / FF 125-1</b>
Available for	all	wheel Ø 100–125 mm	ball bearing versions upon request	all with exception of wheel Ø 80 mm	see versions / options page 212	ball bearing versions	wheel Ø 100+125 mm