

## LUH-GB, BH-GB series

**Pressed steel castors, heavy-duty design, enclosed, with top plate, wheel with Blickle Besthane® polyurethane tread**



800–1,000 kg

**Bracket:** LUH/BH series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free

**Swivel bracket:**


- four-point ball bearing for extremely heavy loads
- enclosed and sealed swivel head
- particularly resistant to shocks and impact due to **specialty-shaped, hardened bearing seats**

**Wheel:** GB series

- tread: high-quality polyurethane elastomer Blickle Besthane®, hardness 92 Shore A, colour brown, non-marking, non-staining
- wheel centre: rugged grey cast iron, with grease nipple from wheel Ø 150 mm, lacquered, colour silver

**Additional details:**

- bracket series: page 93
- brakes: page 112–113
- wheel series: page 312
- bearing types: page 84–85



5

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LUH-GB 128K	BH-GB 128K	LUH-GB 128K-FI	125	60	850	ball bearing	170	140 x 110	105 x 75–80	11	55
LUH-GB 150K	BH-GB 150K	LUH-GB 150K-FI	150	50	800	ball bearing	197	140 x 110	105 x 75–80	11	61
LUH-GB 160K	BH-GB 160K	LUH-GB 160K-FI	160	50	800	ball bearing	202	140 x 110	105 x 75–80	11	61
LUH-GB 200K	BH-GB 200K	LUH-GB 200K-FI	200	50	1,000	ball bearing	245	140 x 110	105 x 75–80	11	63

### Versions / options



	hydrolysis resistant, with cast nylon wheel centre	electrically conductive version, non-marking	directional lock (separate) 1 x 360°	with steel foot guard
Technical description page	56	50	115	116
<b>Product code suffix</b>	<b>GSP0B series</b>	<b>-ELS</b>	<b>RI-05.03</b>	<b>-FS</b>
Available for	upon request	upon request	all*	upon request

\* Only for swivel castors without brake