

## LHD-ALBS, BOD-ALBS series

**Pressed steel twin wheel castors, heavy-duty design, with top plate, wheels with Blickle Besthane® Soft polyurethane tread**



360–800 kg

**Bracket:** LHD/BOD series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free (fixed bracket: solid welded steel construction)
- heavy fork and top plate

**Swivel bracket:**


- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to **four specially-shaped, hardened bearing seats**

**Wheel:** ALBS series

- tread: high-quality polyurethane elastomer Blickle Besthane® Soft, hardness 75 Shore A, colour blue, non-marking, non-staining
- wheel centre: die-cast aluminium, colour silver grey

**Additional details:**

- bracket series: page 93
- wheel series: page 319
- bearing types: page 84–85



5

Swivel castors	Fixed castors	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LHD-ALBS 80K		80	2 x 30	360	ball bearing	115	100 x 85	80 x 60	9	45
	BOD-ALBS 80K	80	2 x 30	400	ball bearing	115	140 x 110	105 x 75–80	11	–
LHD-ALBS 100K	BOD-ALBS 100K	100	2 x 40	640	ball bearing	145	140 x 110	105 x 75–80	11	45
LHD-ALBS 125K	BOD-ALBS 125K	125	2 x 40	740	ball bearing	170	140 x 110	105 x 75–80	11	50
LHD-ALBS 181K	BOD-ALBS 181K	180	2 x 44	800	ball bearing	235	140 x 110	105 x 75–80	11	65

Fixed castors: long side of plate parallel to the wheel axle

### Versions / options



	truck lock
Technical description page	114
Product code suffix	FF 100-1 / FF 125-1 / FF 200
Available for	all from wheel Ø 100 mm*

\* FF 200 suitable for LHD-...wheel Ø 180 mm