

## LI-VEHI, B-VEHI series

**Heat-resistant pressed steel castors with top plate, with heat-resistant Blickle TempLine® Basic wheel with solid rubber tyres**



65–180 kg

-25 °C to +200 °C

**Bracket:** LI/B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Swivel bracket:**

- double ball bearing in the swivel head
- strong central kingpin
- smooth rolling characteristic and low wear, increased service life
- swivel head play is set specifically for high-temperature applications
- highly heat-resistant grease


**Wheel:** VEHI series

- tyre: highly heat-resistant solid rubber, hardness 80 Shore A, colour black
- rim: pressed steel, zinc-plated, blue-passivated, Cr6-free

**Additional details:**

- bracket series: page 97
- brakes: page 112–113
- wheel series: page 442
- bearing types: page 84–85

Blickle TempLine® Basic



Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LI-VEHI 100R	B-VEHI 100R	LI-VEHI 100R-FI	100	30	65	roller bearing	125	100 x 85	80 x 60	9	36
LI-VEHI 125R	B-VEHI 125R	LI-VEHI 125R-FI	125	37.5	90	roller bearing	150	100 x 85	80 x 60	9	38
LI-VEHI 160R	B-VEHI 160R	LI-VEHI 160R-FI	160	40	120	roller bearing	195	140 x 110	105 x 75–80	11	60
LI-VEHI 200R	B-VEHI 200R	LI-VEHI 200R-FI	200	50	180	roller bearing	235	140 x 110	105 x 75–80	11	65