

LI-VKHT series

Heat-resistant pressed steel castors
with top plate, with heat-resistant
Blickle TempLine® Special wheel with solid rubber tyres

 100 kg

 -30 °C to +260 °C

- Bracket:** LI series


 - pressed steel, zinc-plated, blue-passivated, Cr6-free
 - double ball bearing in the swivel head
 - strong central kingpin
 - smooth rolling characteristic and low wear, increased service life
 - swivel head play is set specifically for high-temperature applications
 - highly heat-resistant grease
- Wheel:** VKHT series

 - tyre: highly heat-resistant solid rubber, hardness 85 Shore A, colour black
 - rim: highly heat-resistant nylon 6, impact resistant, colour black
- Additional details:**

 - bracket series: page 97
 - brakes: page 112–113
 - wheel series: page 445
 - bearing types: page 84–85



 **Blickle**
TempLine® Special



Swivel castors	Swivel castors with “stop-fix” brake	Wheel Ø	Tyre width	Load capacity	Bearing type	Total height	Plate size	Bolt hole spacing	Bolt hole Ø	Offset swivel castor
		[mm]	[mm]	[kg]		[mm]	[mm]	[mm]	[mm]	[mm]
LI-VKHT 100G	LI-VKHT 100G-FI	100	30	100	plain bore	125	100 x 85	80 x 60	9	36

Versions / options



	with bolt hole, Ø 13 mm	with bolt hole, Ø 13 mm and “stop-fix” brake
Technical description page	97	112
Product code suffix	LIR-VKHT 100G	LIR-VKHT 100G-FI
Available for		