

LIXR-PHN series

Heat-resistant stainless steel castors with bolt hole, with heat-resistant Blickle TempLine® Classic thermoset wheel

凸 100-150 kg

-35 °C to +260 °C

Bracket: LIXR series

- high-quality chromium-nickel steel (1.4301/AISI 304), stainless steel, vibration-ground finishing
 double ball bearing in the swivel head
- strong central kingpin
- smooth rolling characteristic and low wear, increased service life
- swivel head play is set specifically for high-temperature applications
- highly heat-resistant greasePTFE coated stainless steel axle tube
- · all parts including axle material are corrosion-re-

Wheel: PHN series

- phenolic resin, hardness 90 Shore D, colour black
 Operating temperature from -35 °C to +260 °C, temporarily up to +300 $^{\circ}\text{C}$

Additional details:


- bracket series: page 98
- wheel series: page 463
- bearing types: page 84-85











| Swivel castors | Wheel Ø | Wheel | Load capacity | Bearing type | Total | Plate Ø | Bolt | Offset |
|----------------|---------|-------|---------------|--------------|--------|---------|--------|---------------|
| SWIVEI CASIOIS | WHOOLD | width | Loud dupudity | Doming typo | height | Tido p | hole Ø | swivel castor |
| | [mm] | [mm] | [kg] | | [mm] | [mm] | [mm] | [mm] |
| LIXR-PHN 81G | 80 | 32 | 100 | plain bore | 102 | 70 | 13 | 38 |
| LIXR-PHN 100G | 100 | 30 | 125 | plain bore | 125 | 70 | 13 | 36 |
| LIXR-PHN 102G | 100 | 38 | 150 | plain bore | 125 | 70 | 13 | 36 |
| LIXR-PHN 125G | 125 | 40 | 150 | plain bore | 150 | 70 | 13 | 38 |

Versions / options



| | grease-free swivel head, extremely smooth |
|----------------------------|---|
| Technical description page | |
| Product code suffix | -0F |
| Available for | wheel Ø 100 mm |