

HRLH-SPO, HRLHD-SPO series

Levelling castors with integrated truck lock, with top plate, with heavy-duty nylon wheel



300–600 kg

Bracket: HRLH/HRLHD series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate
- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to **four specially-shaped, hardened bearing seats**
- steel truck lock with rubber pad
- height adjustment with wrench

Wheel: SPO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, extremely robust heavy-duty version, colour natural white

Additional details:

- bracket series: page 101
- wheel series: page 69
- bearing types: page 84–85

Swivel castors	Wheel Ø (D) [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height (H) [mm]	Total height max. (h) [mm]	Displacement (T4) [mm]	Floor clearance foot max. (T3) [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
HRLH-SPO 75K	75	32	300	ball bearing	108	123	15	15	100 x 85	80 x 60	9	55
HRLHD-SPO 75K	75	2 x 32	600	ball bearing	108	123	15	15	100 x 85	80 x 60	9	55

Versions / options



	electrically conductive version, wheel non-marking grey	directional lock (separate) 1 x 360°
Technical description page	50	115
Product code suffix	-EL	RI-04.01
Available for	upon request	HRLH-SPO 75K

