LO-GTH, BO-GTH series

Welded steel heavy-duty castors, wheel with polyurethane tread Blickle Extrathane®

700–1,250 kg

Blickle Extrathane®

Bracket: LO/BO series
- solid welded steel construction, zinc-plated, blue-passivated, Cr6-free

Swivel bracket:
- double ball bearing in the swivel head
- **four specially-shaped, hardened bearing seats** for additional strength
- bolted and secured welded central kingpin, extremely strong
- swivel head seal with labyrinth design
- grease nipple

Wheel: GTH series
- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, colour light brown, non-marking, non-staining
- wheel centre: rugged grey cast iron, with grease nipple from wheel Ø 150 mm, lacquered, colour silver

Additional details:
- bracket series: page 93
- brakes: page 112–113
- wheel series: page 286–287
- bearing types: page 84–85



Swivel castors	Fixed castors	Swivel castor with "stop-top" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LO-GTH 127K	**BO-GTH 127K**	**LO-GTH 127K-ST**	125	50	700	ball bearing	170	140 x 110	105 x 75–80	11	50
LO-GTH 150K	**BO-GTH 150K**	**LO-GTH 150K-ST**	150	50	800	ball bearing	200	140 x 110	105 x 75–80	11	55
LO-GTH 160K	**BO-GTH 160K**	**LO-GTH 160K-ST**	160	50	800	ball bearing	205	140 x 110	105 x 75–80	11	55
LO-GTH 200K	**BO-GTH 200K**	**LO-GTH 200K-ST**	200	50	1,000	ball bearing	245	140 x 110	105 x 75–80	11	60
LO-GTH 201K	**BO-GTH 201K**	**LO-GTH 201K-ST**	200	60	1,250	ball bearing	245	140 x 110	105 x 75–80	11	60
LO-GTH 202K	**BO-GTH 202K**	**LO-GTH 202K-ST**	200	80	1,100	ball bearing	245	140 x 110	105 x 75–80	11	65
LO-GTH 251K	**BO-GTH 251K**	**LO-GTH 251K-ST**	250	50	1,200	ball bearing	295	140 x 110	105 x 75–80	11	70
LO-GTH 250K	**BO-GTH 250K**	**LO-GTH 250K-ST**	250	60	1,200	ball bearing	295	140 x 110	105 x 75–80	11	70

Versions / options

	antistatic version, non-marking grey	with directional lock 4 x 90°	with steel foot guard	truck lock
Technical description page	50	115	116	114
Product code suffix	**-AS**	**-RI4**	**-FS**	**FF 125 / 150 / 160 / 200**
Available for	upon request	wheel Ø 125–200x60 mm	upon request	wheel Ø 125–200 mm