

LHD-ALB, BOD-ALB series

Pressed steel twin wheel castors, heavy-duty design, with top plate, wheels with Blickle Besthane® polyurethane tread



720–900 kg

Bracket: LHD/BOD series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free (fixed bracket: solid welded steel construction)
- heavy fork and top plate

Swivel bracket:


- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to **four specially-shaped, hardened bearing seats**

Wheel: ALB series

- tread: high-quality polyurethane elastomer Blickle Besthane®, hardness 92 Shore A, colour brown, non-marking, non-staining
- wheel centre: die-cast aluminium, colour silver grey

Additional details:

- bracket series: page 93
- wheel series: page 307
- bearing types: page 84–85



Swivel castors	Fixed castors	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LHD-ALB 101K *	BOD-ALB 101K *	100	2 x 40	720	ball bearing	145	140 x 110	105 x 75–80	11	45
LHD-ALB 125K	BOD-ALB 125K	125	2 x 40	900	ball bearing	170	140 x 110	105 x 75–80	11	50
LHD-ALB 181K	BOD-ALB 181K	180	2 x 44	800	ball bearing	235	140 x 110	105 x 75–80	11	65

* Heavy-duty wheel version

Fixed castors: long side of plate parallel to the wheel axle

Versions / options



	truck lock
Technical description page	114
Product code suffix	FF 100-1 / FF 125-1 / FF 200
Available for	all**

** FF 200 suitable for LHD-...wheel Ø 180 mm