

POW series

Low-noise nylon wheels with rubber damping ring

200–220 kg

Tread and tyre hardness



70 Shore D

Smooth operation / floor preservation



satisfactory

Rolling resistance



very good

Wear resistance



good



Tread:

- high-quality nylon 6, impact resistant, hardness 70 Shore D
- low-noise operation (-10 decibels) with elastic cushion layer made from elastic solid rubber, colour red
- easy operation on smooth surfaces
- low rolling resistance
- high abrasion resistance
- colour white

Other features:

- KF version: with synthetic thread guard, large
- high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +80 °C, reduced load capacity over +35 °C

Additional details:

- wheel series: page 69
- tread: page 57
- bearing types: page 84–85
- chemical resistance: page 51

Wheels	Wheel Ø	Wheel width	Load capacity	Bearing type	Axle bore Ø	Hub length
	(D) [mm]	(T2) [mm]			(d) [mm]	(T1) [mm]
POW 100/8KF	100	35	200	ball bearing (C)	8	46
POW 100/10KF	100	35	200	ball bearing (C)	10	46
POW 125/8KF	125	35	220	ball bearing (C)	8	46
POW 125/10KF	125	35	220	ball bearing (C)	10	46

6

Versions / options



large thread guard with additional ball bearing seals

Technical description page

85

Product code suffix

-KFD

Available for

POW 100/8KF +
POW 125/8KF

