

## L-POW, B-POW series

**Pressed steel castors, medium-duty version, with top plate, with low noise nylon wheel**



200–220 kg

**Bracket:** L/B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

**Swivel bracket:**


- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** POW series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour white
- low-noise operation (-10 decibels) with elastic cushion layer made from elastic solid rubber, colour red

**Additional details:**

- bracket series: page 91
- brakes: page 112–113
- wheel series: page 340
- bearing types: page 84–85



Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-POW 100KF	B-POW 100KF	L-POW 100KF-FI	100	35	200	ball bearing (C)	125	100 x 85	80 x 60	9	36
L-POW 125KF	B-POW 125KF	L-POW 125KF-FI	125	35	220	ball bearing (C)	150	100 x 85	80 x 60	9	38

6

### Versions / options



	directional lock (separate) 1 x 360°	large thread guard with additional ball bearing seals
Technical description page	115	85
<b>Product code suffix</b>	<b>RI-03.01</b>	<b>-KFD</b>
Available for	all*	upon request

\* Only for swivel castors without brake