LRXA-TPA, BRXA-TPA, LKRXA-TPA, BKRXA-TPA series

Stainless steel light-duty castors with bolt hole, wheel with thermoplastic rubber tread

50–120 kg

Bracket: LRXA/BRXA, LKRXA/BKRXA series
- high-quality chromium-nickel steel (1.4301/AISI 304), stainless steel, vibration-ground finishing
- all parts including axle material are corrosion-resistant

Swivel bracket:
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: TPA series
- tread: high-quality thermoplastic rubber-elastomer (TPE), hardness 85 Shore A, colour grey, non-marking, oil containing
- wheel centre: high-quality polypropylene, impact resistant, colour silver grey ("-ELS" version colour black)

Additional details:
- bracket series: page 95
- brakes: page 112–113
- wheel series: page 60
- bearing types: page 84–85

INOX



Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LRXA-TPA 50G	**BRXA-TPA 50G**	**LRXA-TPA 50G-FI**	50	19	50	plain bore	69	43	11	23
LRXA-TPA 50KFD	**BRXA-TPA 50KFD**	**LRXA-TPA 50KFD-FI**	50	19	50	ball bearing (C)	69	43	11	23
LRXA-TPA 75G	**BRXA-TPA 75G**	**LRXA-TPA 75G-FI**	75	25	75	plain bore	98	43	11	29
LRXA-TPA 75KFD	**BRXA-TPA 75KFD**	**LRXA-TPA 75KFD-FI**	75	25	75	ball bearing (C)	98	43	11	29
LKRXA-TPA 80G	**BKRXA-TPA 80G**	**LKRXA-TPA 80G-FI**	80	32	100	plain bore	108	57	13	40
LKRXA-TPA 80G-11		**LKRXA-TPA 80G-11-FI**	80	32	100	plain bore	108	57	11	40
LKRXA-TPA 80KFD	**BKRXA-TPA 80KFD**	**LKRXA-TPA 80KFD-FI**	80	32	100	ball bearing (C)	108	57	13	40
LKRXA-TPA 80KFD-11		**LKRXA-TPA 80KFD-11-FI**	80	32	100	ball bearing (C)	108	57	11	40
LKRXA-TPA 101G	**BKRXA-TPA 101G**	**LKRXA-TPA 101G-FI**	100	32	110	plain bore	133	57	13	40
LKRXA-TPA 101G-11		**LKRXA-TPA 101G-11-FI**	100	32	110	plain bore	133	57	11	40
LKRXA-TPA 101KFD	**BKRXA-TPA 101KFD**	**LKRXA-TPA 101KFD-FI**	100	32	110	ball bearing (C)	133	57	13	40
LKRXA-TPA 101KFD-11		**LKRXA-TPA 101KFD-11-FI**	100	32	110	ball bearing (C)	133	57	11	40
LKRXA-TPA 126G	**BKRXA-TPA 126G**	**LKRXA-TPA 126G-FI**	125	32	120	plain bore	158	57	13	40
LKRXA-TPA 126G-11		**LKRXA-TPA 126G-11-FI**	125	32	120	plain bore	158	57	11	40
LKRXA-TPA 126KFD	**BKRXA-TPA 126KFD**	**LKRXA-TPA 126KFD-FI**	125	32	120	ball bearing (C)	158	57	13	40
LKRXA-TPA 126KFD-11		**LKRXA-TPA 126KFD-11-FI**	125	32	120	ball bearing (C)	158	57	11	40

Versions / options



	plain bore version	electrically conductive version, non-marking grey	with synthetic expander fitting, corrosion-resistant	with plug-in stem made of stainless steel	buffers
Technical description page		50	105	104	116
Product code suffix		**-ELS**	**see page 398**	**see page 398**	**AG / ARG series**
Available for		all*	swivel castors with bolt hole Ø 11 mm (except ELS)	swivel castors with wheel Ø 125 mm and bolt hole Ø 13 mm**	see page 398

* Wheel load capacity of electrically conductive version reduced by 35%
** In accordance with DIN 18867-8 (large-scale catering equipment)