

BEV...-ZDG series

Elastic solid rubber press-on bands with steel insert



190–2,700 kg

Tread and tyre hardness
 65 Shore A

Smooth operation / floor preservation
 very good

Rolling resistance
 very good

Wear resistance
 good

Press-on band:

- high-quality elastic solid rubber in smooth rolling quality, hardness 65 Shore A
- very good operational comfort
- low rolling resistance
- very good floor preservation, low-noise operation
- colour black
- steel-wire reinforced
- for wheel centre with outer diameter tolerance h11

Other features:

- high chemical resistance to many aggressive substances, except oils
- operating temperature: -30 °C to +80 °C, temporarily up to +100 °C, reduced load capacity over +60 °C


Additional details:

- wheel series: page 80
- tread: page 53
- chemical resistance: page 51

Press-on bands	Outer Ø	Width	Internal Ø	Load capacity	Load capacity	Load capacity
	(D) [mm]	(T2) [mm]	(d) [mm]	at 4 km/h [kg]	at 10 km/h [kg]	at 16 km/h [kg]
BEV 125x50/75-ZDG	125	50	75	190	130	100
BEV 160x50/100-ZDG	160	50	100	300	200	150
BEV 200x50/140-ZDG	200	50	140	420	280	180
BEV 200x75/100-ZDG	200	75	100	600	400	300
BEV 250x50/190-ZDG	250	50	190	540	360	270
BEV 250x60/170-ZDG	250	60	170	660	440	330
BEV 250x60/190-ZDG	250	60	190	630	420	320
BEV 250x75/140-ZDG	250	75	140	750	500	380
BEV 250x80/170-ZDG	250	80	170	810	540	410
BEV 250x130/140-ZDG	250	130	140	1,270	875	760
BEV 280x50/220-ZDG	280	50	220	630	420	320
BEV 300x75/220-ZDG	300	75	220	900	600	450
BEV 300x85/170-ZDG	300	85	170	960	640	480
BEV 300x90/203-ZDG	300	90	203	1,080	720	540
BEV 360x60/270-ZDG	360	60	270	900	600	450
BEV 360x75/270-ZDG	360	75	270	1,140	760	570
BEV 400x65/305-ZDG	400	65	305	1,080	720	540
BEV 400x75/305-ZDG	400	75	305	1,200	800	600
BEV 405x130/305-ZDG	405	130	305	1,800	1,200	900
BEV 415x90/305-ZDG	415	90	305	1,380	920	690
BEV 425x150/305-ZDG	425	150	305	2,160	1,450	1,100
BEV 500x85/370-ZDG	500	85	370	1,560	1,050	780
BEV 520x100/370-ZDG	520	100	370	1,830	1,225	920
BEV 610x150/410-ZDG	610	150	410	2,700	1,800	1,350

Other dimensions available upon request

Versions / options



	with non-marking natural colour tyre	other versions
Technical description page	53	
Product code suffix	-SN	
Available for	upon request	upon request

